

KDD90VXE

90cm Island Downdraft Hood, Stainless Steel and black glass

EAN13: 8017709203061

- 1 high performance motor, 275W
- Electronic controls
- 4 speeds, plus intensive (10min)
- 1 x 6W LED light
- 2 aluminium grease filters
- Filter cleaning/replacement indicator
- Automatic switch-off
- Internal re-circulation possible
- Non return valve
- Vent outlet Ø 150mm
- Nominal power 275W
- KITRBDD included: Remote motor kit allowing to position motor away from the body of the hood

Speed	I	II	III	IV	Int
Extraction Rate IEC 61591	220	380	450	530	710
Noise Level dB(A) IEC 60704-2-13	46	57	61	65	70

NB: Downdraft extractors can be installed anywhere in a kitchen but are ideal for when a hob is situated in an island unit. The extractor is installed under the worktop directly behind, or to the side of, the hob so that when it is not in use, it can be completely hidden from view. A Downdraft extractor can be vented or recirculated. When it is vented the ducting has to be passed under the flooring, below the cupboards or along the back of the cupboards - it is important therefore to decide on the hood before refurbishment work begins. The length of the ducting will affect the extraction performance, if it has to travel too far to go to an outside wall or there are too many turns in the ducting you are advised to recirculate the extractor.

NB: This model supersedes the KDD90VE

Functions



Options

- **KITFCDD** - Charcoal filter kit for model KDD90VXE
- **RCKF** - Remote control to enable use as ceiling hood
- **SP150** - Simple ducting kit (150mm wide)
- **SP150FLAT** - Comprehensive ducting kit (150mm wide)



Smeg (UK) Limited
3 Milton Park, Abingdon
Oxon OX14 4RN
Tel. +44 (0)844 557 9907
Fax +44 (0)844 557 9337



Lights:

All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting:

when extra fast extraction is required.



Electronic display:

to give a visual reminder of the options selected.



24h:

When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.

90 cm
stainless steel
island chimney hood

